

Performance

Satellite signals tracked simultaneously	GPS: L1 C/A, L2C, L2P, L5
	GLONASS: L1, L2
	BEIDOU: B1, B2, B3, B1C, B2a, B2b
	GALILEO: E1/E5a/E5b/E6
	QZSS: L1/L2/L5/L6
	SBAS: WAAS, EGNOS, MSAS, GAGAN, SDCM
Channels	1408 channels
Cold start	<60 s
Hot start	<15 s
Positioning output rate	1Hz-50Hz
Signal Reacquisition	<1s
RTK Initialization time	<5s
Initialization Reliability	>99.99%
Time accuracy	20 ns

Positioning

Static GNSS surveying	Horizontal: $\pm(2.5\text{mm} + 0.5\text{ppm})$
	Vertical: $\pm(5\text{mm} + 0.5\text{ppm})$
RTK surveying	Horizontal: $\pm(8\text{mm} + 1.0\text{ppm})$
	Vertical: $\pm(15\text{mm} + 1.0\text{ppm})$
Laser surveying	$\pm 1\text{cm} + 5\text{mm/m}$

Communication & Data Storage

I/O interface	USB TypeC
---------------	-----------

Cellular

Integrated full frequency multi band 4G modem, supports WCDMA/CDMA2000/TDD-LTE/FDD-LTE

Bluetooth

Dual-mode Bluetooth

Data Format

Differential data	RTCM2.X, RTCM3.X
GPS output data format	NMEA 0183s RTK, Binary code

1-Precision and reliability may be subject to anomalies due to multipath, obstructions, satellite geometry, and atmospheric conditions. The specifications stated recommend the use of stable mounts in an open sky view, EMI and multipath clean environment, optimal GNSS constellation configurations. Base lines longer than 30 km require precise ephemeris and occupations up to 24 hours may be required to achieve the high precision static specification.



Αποκλειστική διάθεση: **Recap Τοπογραφικός Εξοπλισμός ΕΕ**
 Άνω Τζουμαγιάς 36 Θεσσαλονίκη • 2310 949010 & 210 2601625

Power

Power: 5V/2A
Support USB Type-C fast charging
Internal 1800mAh battery
Battery Life >12 h

Hardware

Physical

Material	Polymer Engineering Materials
Dimensions	136.5x65x56(mm)
Weight	300g
Key	Power button
Indicator	Power indicator, data link indicator, satellite indicator, Bluetooth indicator
Operating temperature	-20°C to +75°C
Storage temperature	-40°C to +85°C
Protection IP	IP67 dust proof, protected from 30min immersion to depth of 1m
Shock	Survive 2 m drop onto the concrete
Vibration	MIL-STD-810G
Humidity	100%, condensing

IMU

IMU	Supported, 4D IMU initialization in 3 seconds
IMU update rate	400Hz
IMU accuracy	<2.5cm within 120°
IMU tilt compensation	0-120°

GUANGZHOU ALPHA GEO-INFO CO.,LTD

Address: Building No.1, Gaopu Road No.68, Tianhe District, Guangzhou 510630, Guangdong, China

Website: www.alphageo-info.com

Email: alphageo@aliyun.com

Phone: +8618565149475



α-GEO



GeoPuls

Handheld Laser RTK



IMU TILT



GSM



WEBUI



FULL GNSS

GeoPuls >>>

GeoPuls is a brand-new RTK instrument with laser function. Its appearance is bold and innovative, and its performance is excellent. Based on the experience of the previous generation of laser equipment, we have made more improvements, including no more frequent calibration, and the use of green laser to solve the problem of difficult to aim in bright light. In a real sense, it realizes measure where you aim, and replacing the pole in the traditional measurement method. However, we are also compatible with the pole mode, which allows the laser measurement to be used even when the pole is used. GeoPuls is a product that surveyors really need.

■ Military-level technology

Military-level processing technology, complete electromagnetic compatibility and shielding technology, minimize system electromagnetic interference, and ensure high-quality observation data and results.




■ Multi constellation

GeoPuls with its 1408 channels new generation full GNSS chipset ability to support multiple satellite constellation including GPS, GLONASS, BEIDOU, GALILEO, OZSS, SBAS and IRNSS provides precise and accurate spatial data for all users around the world.



■ IMU Tilt Sensor

GeoPuls is equipped with a fast initialization, calibration free and immune to magnetic interference inertial Measurement Unit (IMU). All users can use this technology to collect or stakeout topo points up to 120°



■ Laser Survey

The world's exclusive patented laser coordinate measurement quick calibration technology can easily achieve centimeter-level measurement accuracy, making measurement more accurate and user-friendly. Besides the green laser module used in the equipment overcomes the difficulty of aiming under sunlight, making field measurement operations faster and more efficient.



■ Dual-mode Bluetooth

It supports Basic Rate and Enhanced Data Rate operation of traditional Bluetooth, and also supports the latest low-power standard, dual-mode industrial-grade high-speed SPP3.0+ble5.0, suitable for Android/ISO/PC.



■ GSM

A fast internet connection is guaranteed with a built-in 4G module that accelerate receiving correction data using all telecommunication signals and bands.



■ IP67

Strictly measured IP67 waterproof and dustproof grade, sturdy and durable, completely suitable for harsh outdoor environments.

