

MANUAL TOTAL STATION





Efficient Operation
Customizable Hot Keys
Shortcuts
Trigger Button



Trusted Measurement
2" Angle Accuracy
1,500m | 2,000m NP Range
Stable. Reliable



Data Transfer USB drive Bluetooth



Long Duration Smart Battery Manager 3,000mAh Battery 16h working time

SPECIFICATIONS

TELESCOPIC

Length 154mm

Telescopic: 45mm; EMD: 50mm Diameter

Magnification 30x Erect Image Field of View 1°30' 3" **Resolving Power** Minimum Focus 1.5m

DISTANCE

Single Prism Range 5,000m

Accuracy ±(2mm+2mm*D)m.s.e 1,500m | 2,000m (AXIS 2L) Non-prism Range ±(3mm+2mm*D)m.s.e Accuracy Fine: 0.3s; Normal: 0.2s Measuring Time

Auto Sensor Meteorologic Correction Prism Constant Manual

ANGLE

Accuracy

Absolute Encoding Method H: dual; V: dual **Detecting System** 1"/5"/10" Minimum Reading Diameter of Circle 79mm

Zenith: 0°; Horzontal: 0° Vertical Angle 0° 360°/400gon/6400mil Unit

DISPLAY

160*90 with backlight, 6 lines Display Unit

No. of Displays 2

Alphanumeric Keyboard

GUIDE LIGHT

Red+yellow flashing LEDs Type

Workin Range 150m PLUMMET - LASER

Class II red laser Type <0.4mm @ 1.5m height Accuracy

<1.5mm @ 1.5m height Spot Diameter

> *optional - OPTICAL Erect 3X

Magnification 0.3m - ∞ Foucing Range 50 Field of View

TILT CORRECTION

Dual axis Tilt Sensor Method Liquid electric

Range 1" Resolution

LEVEL

Image

30"/2mm Plate Level Circular Level 8'/2mm

DATA INTERFACE

Internal Memory > 10,000 points

Data Interface USB2.0

Bluetooth 2.1, WT12 Wireless

GENERAL

Yes Quick-meas Button

5.4kg Weight

353 (H) * 206 (L) * 200 (W) mm Dimension

Operating Temperature -20°C to 50°C

Li-on battery, 7.4V, 3000mAh

IP55 Water & Dust Proof 16h **Working Duration**



Άνω Τζουμαγιάς 36 • Θεσσαλονίκη www.recap-survey.com • sales@recap-survey.com 2310 949010 • 210 2601625





C-201 Yunsheng Science Park, No.11 Middle Guangpu Road, Huangpu District, Guangzhou 510663, China sales@stecprecision.com support@stecprecision.com







