

Digital Level
DLS-07A

STEC



- High accuracy up to 0.7 mm
- Trigger key
- Measure range: 110m
- IP65 Waterproof and dustproof

SPECIFICATIONS

HEIGHT ACCURACY Standard deviation for 1km of double leveling Electric Reading Optical Reading	0.7mm 1.5mm
DISTANCE Distance Accuracy Distance Range	D<10m: 10mm D>10m: D*0.001 1.5-110m
MINIMUM DISPLAY Height Measurement Distance Measurement	0.01mm/0.1mm/1mm 1mm
MEASURE PERFORMANCE Measuring Time	2.5s
TELESCOPE Magnification Objective Aperture Resolving Power Field of View Multiple Constant Additive Constant	32X 40mm 3" 1°30' 100 0
COMPENSATOR Type Range Accuracy	Magnetic-damped ±15' 0.30"/1'
DATA STORAGE Internal Storage Point Name Connection External Storage	128MB (>30,000 points) Increasing/customized Bluetooth USB Flash disk
LEVEL Circular Vial	8'/2mm
DISPLAY & KEYBOARD Display Keyboard	2.7 inch, 160 x 96 26 keys + 1 trigger button
POWER SUPPLY Battery Operating Time	Rechargeable Li-on Battery, 3400mAh 20h
GENERAL Working Temperature Dimension Weight Water & Dust Proof	-20°C - 50°C 235*200*240mm 2.5kg IP65



GUANGZHOU STAR INFORMATION TECHNOLOGY CO., LTD.

Add:201,Unit 3, Building 2, Yunsheng Science Park, No. 11 Guangpu Middle Road, Huangpu District, Guangzhou, 510663 China
sales@stecprecision.com support@stecprecision.com